



MODEL	A	B	C	D	DEPTH
PB3	4.5	2.75	.625	1.375	3

NOTE: FASTENERS NOT SHOWN ALL DIMENSIONS IN INCHES.



PUSH BUTTON - MODEL PB3:

The Push Button shall be produced by an ISO 9001 certified manufacturer. The Push Button shall be a compact industrial grade 1" by .75" button with protective cowling. The Button shall be labeled 'EXIT' and shall be green back lit using a multi-chip LED. A separate red LED shall be provided as an additional indicator. The LED's shall operate on 12 or 24 VDC (field selectable). The switch shall be DP/ST (field modifiable to DPDT) and rated at 3 Amps at 12 or 24 VDC. The switch shall be available in momentary or alternate action, with a stainless steel single gang face plate or narrow stile stainless steel face plate for mullion mounting. Securiton PB3 (momentary illuminated) or PB3E (momentary non-illuminated) or PB3A (alternate action illuminated) PB3EA (alternate action non-illuminated) or PB3N (momentary illuminated narrow stile) or PB3AN (alternate action illuminated narrow stile) PB3EN (momentary non-illuminated narrow stile) PB3EAN (alternate action non-illuminated narrow stile) PB3ER (surface mount momentary non-illuminated remote receptionist push button) PB3EAR (surface mount alternate action non-illuminated remote receptionist push button)