



SCC-B5300 NTSC

Fixed Dome Color Digital Camera

Specifications

Camera Type	Color	B/W
Image	Device	CCD
	Size	1/3 inch
	Pixels - Total	537 x 505
	Pixel - Effective	510 x 492
Scanning	System	Interlace
	Horizontal Frequency-Internal Mode	15.734 Hz
	Horizontal Frequency Line-lock Mode	15.750 Hz
	Vertical Frequency-Internal Mode	59.94 Hz
	Vertical Frequency-Line-lock Mode	60 Hz
Min. scene Illumination	Color	0.3 Lux
PAN/TILT	Range-Panning	132(Manual)
	Range-Tilting	90(Manual)

Functions	BLC	On
	AGC	On
	ELC	On (Max. 1/100Ksec)
	Line Lock	Off(DC power)/On(AC power)
	White Balance	ATW
Resolution	Horizontal	330 TV Lines
	Vertical	350 TV Lines
Video Output	VBS 1.0Vp-p	VBS 1.0Vp-p
S/N Ratio	S/N Ratio	50dB
Lens	Focal Length	3.8mm
	Aperture Ratio	F2
	Viewing Angle	74°(H) x 54°(V)
Environtal Conditons	Operating Temperature	-10°C ~ +50°C
	Humidity	Less than 90%
Power	Power Requirement	AC24V((G):60Hz/(G)(P):50Hz)±10%, DC12V+10%/-5%
	Power Consumption	3W
Physical Specification	Dimensions (WxHxD) - Net	100(ø) x 67(H) mm
	Weight-Net	180g
	Loading Quantity (20/40ft)	10.560/21.870
	Etc.-Body Color	B5301:Black, B5301G(P):Gray